

Product Description

PU Thinner is a blend of hydrocarbon solvents suitable for dilution of Caparol solvent based polyurethane products to obtain proper paint consistency for application. It is also used for cleaning of tools immediately after application of polyurethane paints.



Recommended Use

PU Thinner is suitable for thinning of solvent based polyurethane paints/coatings

Please note: It is recommended to use trained and experienced applicator.

Physical Properties

Colour	Transparent
Flash Point	> 25° C
Packaging size	5 & 20 litres
Shelf life	12 months

Storage and Handling

12 months when stored in warehouse conditions below 35°C in the original, unopened packs. The product must be kept in in cool, dry well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed and always handle with care. Keep out of reach of children.

Health and Safety

Material can causes serious eye damage. May it cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Do NOT induce vomiting. IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/ attention. Store the material in a well-ventilated place. Keep cool. Do not use or store by hanging on a hook.

Waste Removal

Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. Particular attention should be given to removing wastage from site in compliance with standard construction site procedures. Do not allow product to enter into wadis, waterways, drains, watercourses and soil. Only completely emptied containers should be given for recycling. Material safety data sheet (MSDS) available on request.

Technical Information No. 0108 – Issue: April 2020

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the buyer/user from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. We reserves the right to change the given data without further notice. Our general conditions of sale and delivery in their latest edition apply.